

09298038-091799

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT I, AKEO MARUYAMA, a citizen of Japan residing at Tokyo, Japan have invented certain new and useful improvements in

ELECTRONIC MAIL TRANSMITTING APPARATUS HAVING A
PRINTER DRIVER FOR TRANSMITTING ELECTRONIC MAIL
AND METHOD FOR TRANSMITTING ELECTRONIC MAIL BY
A PRINTER DRIVER

of which the following is a specification:-

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to an electronic mail transmitting apparatus for transmitting document data prepared by an application program via electronic mail and, more particularly, to an electronic mail transmitting apparatus which transmits document data prepared by a specific application program such as a word processor program or an editor program via electronic mail with a simple operation similar to that performed for designating a printing operation. The present invention also relates to a computer readable recording medium which stores a program causing a computer to perform a printer driver function having an electronic mail transmitting function.

2. Description of the Related Art

When a document prepared by a specific application program (hereinafter referred to as an application) such as a word processor program is transmitted via electronic mail, the document can be transmitted as a text of an electric mail. Alternatively, the document is encoded so as to produce an attachment file so that the attachment file can be attached to the electronic mail.

When the document prepared by the specific

application is attached to electronic mail as an attachment file, the receiver side must have the specific application that prepared the document so as to display or print the document on the receiver side.

5 However, in order to display or print the document on the receiver side which does not have the specific application that prepared the document, the document is attached to an electric mail after converting the document data into a general document reader software
10 format such as a portable document format (PDF).

The conversion of the document data format can be done by an independent application exclusive for converting the document data into the general document reader software format. However, in general, a
15 conversion function provided in a printer driver is used. According to the conversion function of the printer driver, document data can be converted into a data format that can be processed by a printer application.

The above-mentioned electronic mail
20 transmission of a document prepared by a specific application is performed according to the following procedure.

First, as shown in FIG.1, a document A stored as a file 1d is retrieved by a specific application such
25 as a word processor application for preparing a document,

093498038-091799

Then, a printer driver 4 is started up, and the document A is converted into a document reader software format by a conversion function of the printer driver 4. The

5 thus-converted document A is stored as a converted file
1e. Thereafter, as shown in FIG.2, an electronic mail
application 5 is started, and an instruction is made to
prepare an electric mail. Then, an E-mail address and a
text of the electronic mail are input. After that, the
10 stored file 1e is attached to the electronic mail, and
the electronic mail is transmitted to a computer network
3.

15 Additionally, when a facsimile modem is
connected to a personal computer (hereinafter referred
to as a PC) so as to perform facsimile transmission by
the PC, a method in which a document prepared by an
application is transmitted by facsimile via a printer
driver may be used. The printer driver having such a
facsimile function may be provided with an address-book
20 function for designating an address and a function for
attaching a facsimile cover letter. Japanese Laid-Open
Patent Application No.8-307702 discloses such a printer
driver.

As mentioned above, in order to transmit via
25 electric mail a document prepared by a specific

application such as a word processor application after converting the document into a data format that can be processed on a receiver side, an application (a printer driver or an application exclusive for conversion)

5 different from the specific application which prepares the document is needed so as to convert the data format of the document. Additionally, an electronic mail application must be started each time an electronic mail is transmitted, and an operation for attaching the
10 converted document to an electronic mail must be performed by a user. Such an operation for converting the document and an operation for preparing the attachment file are annoying work for the user.

15 SUMMARY OF THE INVENTION

It is a general object of the present invention to provide an improved and useful electronic mail transmitting apparatus and method in which the above-mentioned problems are eliminated.

20 A more specific object of the present invention is to provide an electronic mail transmitting apparatus and method which can transmit a document via electronic mail by a simple operation for a user, the document being prepared by a specific application such
25 as a word processor application and an instruction for

09308038-091799

the electronic mail transmission being input through the specific application.

In order to achieve the above-mentioned objects, there is provided according to one aspect of the present invention an electronic mail transmitting apparatus for transmitting document data via electronic mail, the electronic mail transmitting apparatus comprising:

an application program for preparing document data, the application program having a function to send a print instruction to print the document data; and a printer driver activated by the print instruction of the application program, the printer driver having a function to convert the document data provided by the application program into a predetermined data format and a function to transmit the converted document data via electronic mail.

According to the above-mentioned invention, the document data can be transmitted via electronic mail in a manner similar to a manner of a case in which the document data is printed out in accordance with the print instruction sent from the application program. Accordingly, there is no need to perform an annoying operation such as an operation for converting the document data by using an application different from the

09398038-091799

application which prepared the document data or an operation for attaching the converted document data to an electronic mail. Thus, the document data prepared by the application program can be transmitted via

5 electronic mail by a simple operation.

In the electronic mail transmitting apparatus according to the present invention, the printer driver may transmit the converted document data by attaching to an electronic mail as an attachment file.

10 Additionally, in the electronic mail transmitting apparatus according to the present invention, the predetermined data format may be one of a bit map image format, a document reader software format, a text format, a page description language (PDL) format, 15 a hyper text markup language (HTML) format and a standard generalized markup language (SGML) format.

Further, in the electronic mail transmitting apparatus according to the present invention, the printer driver may have a function to manage information 20 regarding electronic mail addresses. The printer driver may also have a function to edit a text of an electronic mail to be transmitted.

Additionally, there is provided according to another aspect of the present invention a method for 25 transmitting document data prepared by an application

09398038-091799

program via electronic mail, the method comprising the steps of:

transferring the document data to a printer driver by sending from the application program a print instruction for printing the document data;

converting the document data into a predetermined data format by the printer driver; and

transmitting the converted document data via electronic mail by an electronic mail transmitting function provided to the printer driver.

According to the above-mentioned method, the document data can be transmitted via electronic mail in a manner similar to a manner of a case in which the document data is printed out in accordance with the print instruction sent from the application program. Accordingly, there is no need to perform an annoying operation such as an operation for converting the document data by using an application different from the application which prepared the document data or an operation for attaching the converted document data to an electronic mail. Thus, the document data prepared by the application program can be transmitted via electronic mail by a simple operation.

Additionally, there is provided according to another aspect of the present invention a processor

099038-091760

readable medium storing program code for causing a computer to perform a function of the above-mentioned printer driver.

Other objects, features and advantages of the present invention will become more apparent from the following detailed description when read in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

10 FIG.1 is an illustration of a structure of a conventional print system;

FIG.2 is an illustration for explaining an electronic mail transmitting operation by a conventional electronic mail application;

15 FIG.3 is a structural diagram of an electronic mail transmitting system according to an embodiment of the present invention;

FIG.4 is an illustration showing an electronic mail transmitting operation performed by a personal computer shown in FIG.3;

FIG.5 is an illustration for explaining the electronic mail transmitting operation performed by the personal computer shown in FIG.3;

FIG.6 is a flowchart of an operation performed by a printer driver shown in FIG.3;

093933-8206650

FIG.8 is an illustration of the printing
5 method designating screen presented by the printer
driver shown in FIG.3:

FIG.10 is an illustration of the mail
10 designating screen presented by the printer driver shown
in FIG.3;

FIG.11 is an illustration of the mail designating screen presented by the printer driver shown in FIG.3;

15 FIG.12 is an illustration of the printing
method designating screen presented by the printer
driver shown in FIG.3; and

FIG.13 is a perspective view of a personal computer that is configured to execute software stored on a processor readable medium.

A description will now be given, with
reference to FIGS.3, 4 and 5, of a first embodiment of
25 the present invention. FIG.3 shows a structure of an

electronic mail transmitting system according to the first embodiment of the present invention. As shown in FIG.3, in the electronic mail transmitting system according to the present embodiment, a personal computer (PC) 1 and a printer 2 are connected to each other so that bidirectional communication can be performed therebetween. The PC 1 is connected to a computer network 3 so that the PC 1 can send an electronic mail to a remote computer via the computer network 3.

A specific application 1a such as a word processor application, a graphics processing module 1b and a printer driver 1c are installed to the PC 1. The graphics processing module 1b constitutes a part of an operating system (OS) of the PC 1.

A description will now be given, with reference to FIGS.3, 4 and 5, of a process for sending an electronic mail by the application 1a such as a word processor application in the electronic mail transmission system according to the present embodiment in which the OS is operating on the PC 1.

When a document prepared by the application 1a is printed by the printer 2, the printer driver 1c is started by a print instruction sent from the application via the graphics processing module 1b. Then, the document data designated for printing by the application

0939038-09199

1a is converted into a page description language (PDL) format. The converted document data is provided from the PC 1 to the printer 2, and a printing operation is performed by the printer 2. The page description

5 language format is a data format which can be processed by the printer 2. That is, the printer 2 is capable of printing an image representing the contents of the document data of the page description language format.

As mentioned above, a regular printing
10 operation is performed in the same manner as the conventional printing operation. Additionally, in the present embodiment, when the document data prepared by the application 1a is sent via electric mail, an
15 instruction for sending an electronic mail is sent from the application 1a, as shown in FIG.4, in the same manner as the printing operation. Then, the document data is converted into a specific data format by a data format converting function of the printer driver 1c so that the converted document data can be displayed and
20 printed on a remote terminal receiving the electronic mail. Thereafter, the electronic mail is transmitted by an electronic mail transmitting function provided in the printer driver 1c. The converted document data is incorporated in the electronic mail as a text of the
25 electronic mail or an attachment file.

095038-091799

When an electronic mail is sent by the application 1a, as shown in FIG.5, document data A stored in an application document file 1d is retrieved by the application 1a, and the application 1a sends a
5 print instruction for the document data A. Then, the printer driver 1c is started, and the retrieved document data A is converted into data having the specific data format by the data format converting function of the printer driver 1c so that the data having the specific
10 data format can be displayed and printed on a remote terminal receiving the electronic mail. Thereafter, the converted document data A is transmitted to the computer network 3 as an attachment file of the electric mail. The specific data format of the converted document data
15 A may vary according to an electronic mail application of the receiver, a specification of a binary data processing method on the computer network 3 or a characteristic of data after conversion. In the present embodiment, the specific data format is the same as a
20 data format that is used in a case in which data to be transmitted is encoded to data represented by only text by a conventional electronic mail application and the encoded data is transmitted as an attachment file of an electronic mail.

25 As mentioned above, in the present embodiment,

09350338-091799
552760-88085550

the document data A can be transmitted via electronic mail in a manner similar to a manner of a case in which the document data A is printed out in accordance with the print instruction sent from the application 1a.

5 Accordingly, there is no need to perform annoying operations such as converting the document data A by using an application different from the application 1a which prepared the document data A or attaching the converted document data A to an electronic mail. Thus,
10 the document data prepared by the application 1a can be transmitted via electronic mail by a simple operation.

In the above-mentioned embodiment, a bit-map image format may be used as the specific data format so as to transmit the converted document data A via
15 electronic mail and display or print the converted document data A on the receiver side. That is, the document prepared by the application 1a is developed in a bit-map image by the printer driver 1c, and the developed bit-map image is converted into a bit-map
20 image format which can be developed on the receiver side. Then, the converted bit-map image data is transmitted via electronic mail by being attached as an image file. Accordingly, the image file attached to the electronic mail can be displayed on a monitor or printed by a
25 printer on the receiver side by developing the image

09398038-091799

file on a bit-map.

A series of processes for attaching the bit-map image file is similar to processes performed by a facsimile modem for transmitting a document prepared by an application. However, the transmission of the developed image in the present embodiment is different from that of the facsimile transmission in that the present embodiment uses electronic mail while the facsimile modem uses facsimile transmission.

10 Additionally, a document reader software format used by a generally used document reader software such as the Acrobat Reader [™] may be used as the specific data format so as to transmit the converted document data A via electronic mail and display or print the
15 converted document data A on the receiver side. The Acrobat Reader [™] is an application for reading a portable document format (PDF) file. That is, the document data prepared by the application 1a is converted into the document reader software format by
20 the printer driver 1c, and the thus-converted document data is transmitted as an attachment file via electronic mail. Thereby, the attachment file attached to the electronic mail can be processed by the document reader software on the receiver side. Although a process is
25 dependent on the document reader software provided to

the receiver side, generally the attachment file can be displayed and edited by the document reader software and printed by the printer.

5 Additionally, a text format may be used as the
specific data format so as to transmit the converted
document data A via electronic mail and display or print
the converted document data A on the receiver side.
That is, the document data prepared by the application
1a is converted into the text format by the printer
10 driver 1c, and the thus-converted document data is
transmitted as an attachment file via electronic mail.
In such a case, the text data corresponding to the
converted document data can be added to a text of the
electronic mail or attached to the electronic mail as an
15 attachment file.

On the receiver side, the text of the
electronic mail or the text file attached to the
electronic mail can be displayed, printed or edited by
an electronic mail software or an editor software.

20 Since the converted document data contains
only text format data, there may be a case in which a
part of the document prepared by the application 1a
cannot be converted. However, since the converted data
contains only text format data, it is assured that the
25 entire converted data can be processed by a different

09393033-091799

application. Additionally, transmission of an electronic mail using text format data can be performed by a word processor application that is usually used by a user without using electronic mail software.

5 Further, a page description language (PDL) format may be used as the specific data format so as to transmit the converted document data A via electronic mail and display or print the converted document data A on the receiver side. That is, the document data
10 prepared by the application 1a is converted into the page description language format by the printer driver 1c, and the thus-converted document data is transmitted via electronic mail. In such a case, the converting process is similar to the process performed by the
15 printer driver when printing. The page description language format data can be added to a text of the electronic mail or attached to the electronic mail as an attachment file. On the receiver side, the page description language format data can be output by a
20 printer that can read the page description language format data.

 Additionally, an electronic document format such as a hyper text markup language format (HTML) format or a standard generalized markup language (SGML)
25 format may be used as the specific data format so as to

09393033-091799

transmit the converted document data A via electronic mail and display or print the converted document data A on the receiver side. That is, the document data prepared by the application 1a is converted into the

5 HTML format or the SGML format by the printer driver 1c, and the thus-converted document data is transmitted via electronic mail. The HTML format data or the SGML format data can be added to a text of the electronic mail or attached to the electronic mail as an attachment

10 file. On the receiver side, the HTML format data or the SGML format data can be displayed, printed or edited by electronic mail software or Web browser.

In the above-mentioned embodiment, when the printer driver 1c is started, an input operation window

15 of the printer driver 1c is displayed on a display unit of the PC 1. An electronic mail address should be input through the input operation window. Accordingly, an information managing function (address-book function) for managing information regarding electronic mail

20 addresses is provided to the printer driver so that a user can input a desired electronic mail address by selecting the address from among electronic mail addresses managed by the printer driver 1c through the operation window. For example, a plurality of

25 previously registered electronic mail addresses are

09398038-091799

displayed on the input operation window so that the user can designate one of the displayed electronic mail addresses on the input operation screen.

Additionally, an editing function may be
5 provided to the print driver 1c so as to edit a text of the electronic mail including the converted document data. That is, additional information such as a comment to the document can be included in the same electronic mail. In order to achieve such a function, a template
10 corresponding to a letter head of an electronic mail may be provided so that the user can select the template so as to input or edit information regarding a description or memo of the document to be transmitted by the electronic mail. Such a description or memo is
15 transmitted as a text of the electronic mail together with the converted document data which is attached as an attachment file to the electronic mail.

The printer driver 1c can be installed to an electronic apparatus such as document preparing
20 apparatus having an electronic mail transmitting function or a personal computer having an electronic mail application and a word processor application. According to an electronic apparatus in which the printer driver is installed, a document prepared by the
25 word processor application can be transmitted via

0939030109390301

electronic mail in the same manner as a printing operation for printing the prepared document by the word processor application.

As shown in FIG.13, the printer driver 1c may
5 be stored in a recording medium such as a CD-ROM 7 so that the printer driver 1c can be installed to an electronic apparatus such as the personal computer 1 from the CD-ROM 7. The recording medium may be in other forms such as a floppy disk (FD), a magnetooptical disk
10 (MO) or a mini-disk (MD). Such an electronic apparatus in which the printer driver 1c is installed can perform the same electronic mail function as the PC 1 according to the above-mentioned embodiment of the present invention. Additionally, by installing the printer
15 driver 1c stored in a recording medium to a plurality of personal computers via a network, a communication system having a plurality of terminals provided with the above-mentioned electronic mail function according to the present invention can be constructed.

20 A description will now be given, with reference to FIG.6, of an operation of the printer driver 1c according to the above-mentioned embodiment of the present invention. FIG.6 is a flowchart of an operation of the printer driver 1c. It is assumed that
25 the printer driver 1c is provided with a function to

09303360" 8E036E60

convert document data into a page description language (PDL) format, a function to convert document data into an image data format and a function to convert document data into a text format.

5 When a print instruction for the document data is sent from the application 1a, the printer driver 1c is activated or started. This process is the same as the conventional print instruction. That is, the printer driver 1c has an interface with the OS of PC
10 which interface is the same as that of a conventional printer driver. Accordingly, the user inputs a print instruction through the application even when the user intends to transmit the document data via electronic mail.

15 When the operation of the printer driver is started, it is determined, in step S1, whether or not the document data which is designated for printing is designated for regular printing or electronic mail transmission. That is, when the printer driver 1c is
20 activated or started, a print dialogue window is displayed on a display unit of the PC 1. When the user elect a property of the print dialogue, a user interface screen (a printing method designating screen) is displayed as shown in FIG.7.

25 When the user intends to print the document

0938030179
552750"8308550

data by the regular printing, the user designate the regular print on the screen shown in FIG.7 and click an OK button. Then, the print dialogue window appears again and the regular printing operation is performed.

- 5 That is, if it is determined, in step S1, that the regular printing operation is designated, the routine proceeds to step S2. In step S2, the document data provided by the application 1a is converted into the page description language format. Then, in step S3,
- 10 information regarding a printer to be used for printing is obtained. Thereafter, in step S4, the document data which was converted into the page description language format is sent to the printer 2, and the routine is ended. Accordingly, the document data is printed out by
- 15 the printer 2.

As mentioned above, the printer driver 1c has a function as a conventional printer driver, and the interface with the OS installed in the PC 1 is the same as that of a conventional printer driver.

- 20 A description will now be given of an operation of transmitting the document data by the printer driver 1c. If it is determined, in step S1 of FIG.6, that the mail transmission is designated, the routine proceeds to step S5. That is, in the user interface screen shown in
- 25 FIG.7, if the user designates the mail transmission and

In step S5, it is determined whether or not the document data is to be converted into the page description language format. If it is determined that the document data is to be converted into the page description language, the routine proceeds to step S6. In step S6, the document data is converted into the page description language format.

20 On the other hand, if it is determined, in
step S7, that the document data should not be converted
into the bit-map image format, the routine proceeds to
step S9. In step S9, the document data is converted
into a text format.

25 The above-mentioned process for selecting the

That is, in the screen shown in FIG.8, when the user designates the mail transmission and clicks the OK

0 Accordingly, if the user intends to designate the page
description language format, there is no need to
designate the PDL format on the screen. If the user
intends to designate one of other data formats, the user
clicks a transmission data format designating button on
15 the screen so as to display selectable data formats.
FIG.10 shows the mail designating screen on which the
selectable data formats are displayed. In this case,
the PDL, the image and the text are displayed on the
screen as selectable data formats. If the user selects
20 and clicks the image, the bit-map image format is
designated as the data format of the document data to be
transmitted.

Returning to FIG.6, when the process of step
S6, step S8 or step S10 is completed, the routine
25 proceeds to step S10. In step S10, a mail address to

which the electronic mail is transmitted is obtained.

Specifically, the mail address to which the electronic mail is transmitted is set by the user designating one of mail addresses displayed on the mail designating screen shown in FIGS.9, 10 and 11. Since the printer driver 1c is provided with the managing function for managing information regarding mail addresses, addition, deletion and edition of the registered mail addresses can be performed by clicking the edit button on the mail designating screen. When the user clicks the OK button after designating one of the data formats and designating one of the mail addresses on the mail designating screen, the user interface screen appears again. At this time, the designated mail address and the designated data format are displayed as shown in FIG.12.

After the process of step S10 is completed, the converted document data is sent to a mail server as an electronic mail in step S11, and the operation of the printer driver 1c is ended.

It should be noted that the designation of the mail address by the process of step S10 may be performed before the designation and conversion of the data format by the process of steps S5 to S9.

Additionally, a designation as to whether the

converted document data should be transmitted as a text of an electronic mail or as an attachment file attached to the electronic mail may be performed in the process of the printer driver 1c.

5 The present invention is not limited to the specifically disclosed embodiments, and variations and modifications may be made without departing from the scope of the present invention.

10

15

20

25

0939038-091799
1562760-8308560